Fujitsu recommends Windows® 7.

Data Sheet
Fujitsu ESPRIMO E500 E85+ Desktop PC

Your Flexible Economy PC

Fujitsu All-round ESPRIMO PCs deliver high-quality computing for your office applications and projects at a very attractive price point. You can choose cost-optimized fixed configurations for immediate delivery. Alternatively, you can use configuration options to meet your specific hardware needs, while staying within your budget.

Intelligent performance and best price/performance ratio
Cost-effective system for large enterprise projects
- 2nd generation Intel® Core™ processors with Turbo Boost 2.0 and Hyper-Threading technology

Flexibility
Freedom of choice with tailored systems, perfect fit for specific requirements
- Flexible logistics concept - Customizing program (made4you)

Reliability
Excellent quality and functional stability
- Proprietary development and production in Europe

Lifecycle
Hardware continuity for long-lasting project requirements
- Managed lifecycle up to 12 months

Meets ENERGY STAR® and Blue Angel requirements
Low power consumption and low costs, without any loss in performance
- Up to 86% energy efficient power supply

Fujitsu recommends Windows® 7.

Components

Processor	Intel® Core™ i7-2600 processor (4 Cores / 8 Threads, 3.40 GHz, 8 MB, Intel® HD Graphics 2000)
	Intel® Core™ i5-2500 processor (4 Cores / 4 Threads, 3.30 GHz, 6 MB, Intel® HD Graphics 2000)
	Intel® Core™ i5-2400 processor (4 Cores / 4 Threads, 3.10 GHz, 6 MB, Intel® HD Graphics 2000)
	Intel® Core™ i3-2120 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2000)
	Intel® Core™ i3-2100 processor (2 Cores / 4 Threads, 3.10 GHz, 3 MB, Intel® HD Graphics 2000)
	Intel® Pentium® processor G840 (2 Cores / 2 Threads, 2.80 GHz, 3 MB, Intel® HD Graphics)
	Intel® Pentium® processor G620 (2 Cores / 2 Threads, 2.60 GHz, 3 MB, Intel® HD Graphics)
	Intel® Celeron® processor G530 (2 Cores / 2 Threads, 2.40 GHz, 2 MB)
Operating systems	
Operating system	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Operating system compatible	openSUSE Linux Genuine Windows Vista® Genuine Windows® XP
Operating system notes	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com
Memory modules	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
	4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
Hard disk drives (internal)	SSD SATA, 256 GB, 2.5-inch
	SSD SATA, 128 GB, 2.5-inch
	HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 320 GB, 3.5-inch
	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch
Hard disk notes	Up to 18 GB of HDD space is reserved for system recovery
Graphics add on cards (optional)	NVIDIA® Quadro® NVS 300 LP, 512 MB
	NVIDIA® GeForce® GT 420
	NVIDIA® GeForce® 405 display port low profile, 512 MB
	LFH59/ 2x DVI-I adapter cable
	LFH59/ 2x DP adapter cable
	DP to DVI-D (single link) Adapter Cable
Drives (optional)	Blu-ray Disc™ Triple Writer
	DVD-ROM
	DVD Super Multi
	MultiCard Reader 20in1, USB 2.0, 3.5-Inch
	MultiCard Reader 20in1 USB 3.0 front con., 3.5-Inch
Interface add on cards/components (optional)	
	WLAN III, 802.11g/Draft-n (Windows only)
	USB 3.0 PCIe x1
	Parallel Interface
	Gigabit Ethernet PCIe x1, DS
	eSATA Interface
	Dual serial card PCIe x1, powered
	Dual serial card PCIe x1

Base unit	ESPRIMO E500 E85+
Mainboard	
Mainboard type	D2991
Formfactor	ATX
Chipset	Intel® B65
Processor socket	LGA 1155
Processor quantity maximum	1
Memory slots	4 DIMM (DDR3)
Supported capacity RAM (max.)	32 GB
Memory frequency	1333 MHz
Memory notes	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules
LAN	10/100/1000 MBit/s Realtek RTL 8111E
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio codec	Realtek ALC663
Audio features	High Definition Audio
I/O controller on board	
Serial ATA total	4
thereof SATA III	1
thereof eSATA	1 (optional)
Controller functions	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI
Interfaces	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	10
USB 3.0 total	optional
USB front	2
USB rear	6
USB internal	2
VGA	1
DVI	1 (DVI-D)
Serial (RS-232)	1 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality
Input device / components	
	Optical USB wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse KBPC PX ECO Mouse M440 ECO

Drive bays	
Drive bays total	3
3.5-inch internal bays	1
3.5-inch external bays	1
5.25-inch external bays	1
Drive bay notes	optional external bay as internal 3,5"
Slots	
PCI-Express 2.0 x16	1 x (200 mm) Low profile
PCI-Express x1	2 x (174 mm) Low profile
PCI (32-bit / 33 MHz)	1 x (174 mm) Low profile
Graphics on board	
Graphics brand name	Intel® HD Graphics 2000
Shared video memory	up to 1759 MB
TFT resolution (VGA)	1024 x 768 pixel 1280 x 1024 pixel 1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1600 x 1200 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
Graphics features	Dual display support DirectX 10.1 HDCP support OpenGL® 2.1 For multi monitoring mode, graphics card and integrated graphics run in parallel (Microsoft® Windows 7® only)
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz
Electrical values	
Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 83% / 86% / 85%
	0-Watt mode with hard-off switch
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power	active
Monitor outlet	No
Power consumption	
Power consumption note	See white paper Energy Consumption 0-Watt mode with hard-off switch
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=ab648c08-c3d1-4e6e-8c41-ededc1e8fab8
Heat dissipation	
Heat dissipation notes	See white paper Energy Consumption

Noise for standard configuration (HDD, ODD)	
Noise emission	According to ISO9296
Related Processors for noise	Intel® Core™ i5 2400
Noise Operation mode 1: ODD load (Blue angel requirement)	4.1 B/ 26 dB(A)
Noise Operation mode 2: HDD load (Blue angel requirement)	3.7 B/ 23 dB(A)
Noise Operation mode 3: CPU 90% load (Blue angel requirement)	4.4 B/ 29 dB(A)
Noise Operation mode 4: High load	4.4 B/ 30 dB(A)
Noise Operation mode 5: Office applications 2.0	3.7 B/ 22 dB(A)
Idle mode (Blue Angel requirement)	3.7 / 22 dB(A)
Noise notes / description	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position
Dimensions / Weight / Environmental	
Dimensions (W x D x H)	340 x 382 x 98 mm
Operating position	Vertical / horizontal (optional, feet needed)
Weight	approx. 10 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35°C
Compliance	
Product	ESPRIMO E500
Model	DT8-2991
Germany	Blauer Engel / Blue Angel in progress TÜV GS
Europe	CE Nordic Swan
USA/Canada	FCC Class B cCSAus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® EPEAT® Gold (dedicated regions)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/
Additional Software	
Additional software (preinstalled)	Nero Essentials S (burning software) Fujitsu Recovery (Hard Disk Based Recovery) Norton Internet Security (incl. Firewall) 60 days version Microsoft® Office Starter: reduced-functionality Word and Excel® only, with advertising. No PowerPoint® or Outlook®. Buy Office 2010 to use the full-featured software.
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive / Blu-ray playback is not supported under Windows XP if the system runs on Intel onboard graphics)
Miscellaneous	
	Thermal management
Compatibility (references)	
	DMI 2.0 PC 2001 WMI 1.5 USB 2.0 SMBIOS

Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode)
DeskView components	WoL (Wake on LAN)
Manageability link	http://ts.fujitsu.com/manageability http://www.altiris.com/fujitsu
Security	
System protection	Kensington Lock support Eye for padlock
Audit proof protection	Boot sector virus protection Write protect option for the Flash EPROM Control of external interfaces
Access protection	User and supervisor BIOS password Hard disk password Optional: Access protection via external SmartCard reader Optional: Access protection via internal SmartCard reader
Serviceability	
	EasyFix EasyChange for HDD EasyChange for optical drives
Packaging information	
Packaging dimension	467x265x540 mm
Max. quantity / pallet	28
Material - Weight (g) Carton	1140 g
Material - Weight (g) EPS / PS	180 g
Material - Weight (g) PE	appr. 60 g
Packaging notes	printed user documentation is bleached in chlorine free process
Warranty	
Standard Warranty	1 year
Service level	Bring-In / On-Site Service (depending on country)
Maintenance and Support Services - the perfect extension	
Recommended Service	5x9, Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	http://ts.fujitsu.com/Supportservice

More information

Fujitsu platform solutions

In addition to Fujitsu ESPRIMO E500 E85+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures
With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products
www.fujitsu.com/global/services/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO E500 E85+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
http://ts.fujitsu.com/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at http://www.fujitsu.com/global/about/environment/

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact
FUJITSU Technology Solutions
Website: http://ts.fujitsu.com
2011-10-28 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions